VFRSA

ONE EASY-TO

INSTALL PANEL



SNAP LOCK *Clip Series* STANDING SEAM METAL PANEL SYSTEMS

SLEEK MODERN LOOKS & POWERFUL PERFORMANCE

Combining bold standing seam lines and ease of installation, a Snap Lock Clip system delivers enhanced thermal movement and wind resistance. Concealed metal clips snap together with panels to form an interlocking seam that holds them in place no mechanical seaming required!

PRODUCT ATTRIBUTES

- Hidden fasteners and clips
- ✓ Allows for thermal movement
- Excellent wind uplift resistance
- 🗸 Lock-action design requires no mechanical seaming
- Unlimited panel lengths with on-site panel manufacturing
- Available in steel and aluminum in 50+ colors (copper & zinc optional)
- ✓ Striated*, ribbon bead or pencil bead
- ✓ Finish warranties[†] up to 50 years / Metal warranties[†] up to 25-1/2 years

YOUR ONE STOP SHOP FOR METAL ROOFING. STRENGTH YOU CAN TRUST.

Proudly finished with your choice of Kynar 500[®] (70% PVDF), WeatherXL™ (SMP), Acrylic-coated Galvalume[®] or Tedlar[®] PVF film

SNAP LOCK Clip Series STANDING SEAM METAL PANEL SYSTEMS

IM675SL 1-3/4" Snap Lock Clip Panel Coverage Width: 14", 16" or 18" [†]Slope: 1/4:12 minimum Rib Height: 1-3/4" Metal/Gauge: 26- and 24-Gauge Galvalume; 22 Gauge Special Order / .032 and .040 Aluminum (Additional gauges and copper and zinc available with site-specific certification) Support: Plywood or Wood Plank IM550SL 1-1/2" Snap Lock Clip Panel **Coverage Width: 15", 17" or 19"** [†]Slope: 1/4:12 minimum Rib Height: 1-1/2" Metal/Gauge: 26- and 24-Gauge Galvalume / .032 and .040 Aluminum (Additional gauges and copper and zinc available with site-specific certification) Support: Plywood or Wood Plank IM450SL 1-1/2" Snap Lock Clip Panel Coverage Width: 15.5" [†]Slope: 1/4:12 minimum Rib Height: 1-1/2" 15-1/2" Coverage Metal/Gauge: 26- and 24-Gauge Galvalume (Additional gauges and copper and zinc available with site-specific certification) Support: Plywood or Wood Plank Connect with Us! @integritymetalsfl All panels are Florida Product Approved including HVHZ on most profiles (\mathbf{k}) [‡] Sealant maybe required. 🔛 integritymetalsfl.com

Ontegrity Metals LLC. *All snap lock panels come standard with striations unless otherwise specified or requested. †Talk with an Integrity Metals representative for full warranty details and restrictions. ‡ Minimum slope with sealant per FBC 1507.4.2; consult with local municipality for applicable controlling building codes that may affect your project. Galvalume® is a registered trademark of BIEC International Inc. Kynar 500° is a registered trademark of Arkema Inc. WeatherXL® is a registered trademark of The Sherwin Williams Corporation. Tedlar® is a registered trademark of Arkema Inc. affiliates of DuPont de Nemours, Inc. and is used under license by Titan Steel Corporation and its affiliates.

🔁 sales@integritymetalsfl.com

C 772-584-2654